Self-Retracting Lifeline*

To DIN EN 360:2002



Specification ← The retractable lifeline offers a high degree of mobility and flexibility of use. The quick-action braking system works similar to a car safety belt. The mechanism keeps the cable, connected to the anchor point, under tension and guarantees an immediate stop function when necessary.

- Durable and low-maintenance retractable lifeline with galvanised steel cable
- Rotary swivel prevents twisting of the cable
- Lightweight and durable high-impact plastic housing
- Including karabiner double action hook and Ø 16 mm swivel eye, to connect the unit to the anchor post or anchorage line with a karabiner to DIN EN 362
- -Approved for vertical or horizontal use, tested for fall over edge



WG 1122 ←	Туре	Cable Length	Housing	Weight	Dimensions [mm]	Product No.
	Retractable Lifeline HWPS 4,5	4.5 m cable	Plastic	2.1 kg	400 x 130 x 78	768-IKHWPS45
	Retractable Lifeline HWPS 6	6.0 m cable	Plastic	2.5 kg	420 x 145 x 80	768-IKHWPS6
	Retractable Lifeline HWPS 12	12.0 m cable	Plastic	4.9 kg	500 x 195 x 95	768-IKHWPS12

Equipment Bag*

Equipment Cabinet*

 ${\color{red}\mathsf{Specification}} \leftarrow \quad \mathsf{For} \; \mathsf{the} \; \mathsf{safe} \; \mathsf{storage} \; \mathsf{and} \; \mathsf{transport} \; \mathsf{of} \;$ safety equipment, ropes, lanyards and harnesses. Made of sturdy fabric.

Dimensions: Ø 30 cm, height 60 cm

For the safe storage of safety equipment.

- Made of steel sheet metal
- For wall fastening, two mounting rods included
- Lockable
- Dimensions: 50 x 35 x 22 cm





WG 1122 ←	Туре	Product No.		
	Equipment Baa	768-IKBG		

Туре	Product No.		
Equipment Cabinet	768-ARGS		

^{*} Fall Protection Systems cannot be returned. Status: 03/22 b/s/t GmbH Koch Kunststofftechnologie reserves the right to make technical modifications.