## **Rescue Kit\***

Specification ←

Controlled descent rescue system with casualty lifting and remote reach capabil- - Steel IKV 13 screw-gate karabiner a ities; tested and certified in Germany to conform to the relevant European Standards. Designed for workers using full body fall arrest harnesses in conjunction with energy-absorbing lanyards or retractable-type devices. The Rescue Kit offers a compact, fully assembled and easily transported rescue unit. Using a lifting and releasing rescue action, the ABS3WH Rescue Kits are "NO CUT" rescue systems.

## The kit contains

-ABS3WH controlled descent device with rescue lifting facility or automatic speed regulation for lowering off

- -1.0 m webbing anchorage sling
- connection device
- Remote reach pole 307 x 2.5 x 2.5 cm (extended), 81 x 2.5 x 2.5 cm (retracted), with clamp to keep the rope karabiner hook in open position
- -10 mm diameter kernmantle rope with small double-action hooks at each end
- -Available in two lengths of rope: 20.0 m or 40.0 m
- Edge rope protection plate for rescue application over roof edge
- Purpose-made rescue tackle bag
- Detailed information/instruction card
- -Weight only 6.2 kg

Rescue distance up to 5.0 m



WG 1122 ←	Туре	Product No.
	Rescue Kit 20 m	768-IKRS20
	Rescue Kit 40 m	768-IKRS40

<sup>\*</sup> Fall Protection Systems cannot be returned.

Status: 03/22 b/s/t GmbH Koch Kunststofftechnologie reserves the right to make technical modifications.